


**NOTE A:** When sound wall as measured from the bottom of the gate opening exceeds 6'-8" or 7'-0", see 5'-0" GATE DETAILS (2) sheet.



1. Gate mounted on sloping grade shall be oriented to be in closed position when at lower grade point.
2. Two masonry cells adjacent to each side of gate to be reinforced and grouted.



For location of nylon finishing washers,  
see Standard Plan B15-11.




SECTION D-D  
CHANNEL MOUNTING HOLE

STATE OF CALIFORNIA  
DEPARTMENT OF TRANSPORTATION

**SOUND WALL MASONRY BLOCK  
ON FOOTING OR PILE CAP  
5'-0" ACCESS GATE  
DETAILS (1)**

**B15-10**

DIST	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET NO.	TOTAL SHEET

  
 REGISTERED CIVIL ENGINEER

October 30, 2015  
 PLANS APPROVAL DATE

THE STATE OF CALIFORNIA OR ITS OFFICERS  
 OR AGENTS SHALL NOT BE RESPONSIBLE FOR  
 THE ACCURACY OR COMPLETENESS OF SCANNED  
 COPIES OF THIS PLAN SHEET.

REGISTERED PROFESSIONAL ENGINEER

Tiliot Sartre

NO. C42892

EXP. 3-31-16

CIVIL

STATE OF CALIFORNIA